

MUL-0005

### IN THE CLAIMS

1. (previously presented) A retrofit LED light tube for replacing a fluorescent light tube in a troffer fixture, the LED retrofit light tube comprising:

an elongated cylindrical transparent envelope;

a base cap at each end of the envelope, wherein the base cap comprises a first prong and a second prong extending from the base cap, wherein the first and second prongs are adapted to electrically communicate with a fluorescent light socket; and

at least one LED device in electrical communication with the base cap, wherein a positive terminal of the LED device is in electrical communication with the first prong and a negative terminal is in electrical communication with the second prong, wherein the at least one LED device consists of organic light emitting diodes.

2. (canceled)

3. (original) The retrofit LED light tube of Claim 1, wherein the at least one LED device are connected in parallel to additional LED devices.

4. (original) The retrofit LED light tube of Claim 1, further comprising a means for protection against a voltage surge.

MUL-0005

5. (original) The retrofit LED light tube of Claim 4, wherein the means for protection against a voltage surge comprises a varistor positioned in parallel with the at least one LED device.
6. (original) The retrofit LED light tube of Claim 1, wherein the LED device comprises a circuit board and a plurality of LEDs serially connected to the circuit board.
7. (original) The retrofit LED light tube of Claim 1, wherein the envelope comprises a first half and a second half, wherein the halves are complementary and adapted to form the envelope.
8. (original) The retrofit LED light tube of Claim 1, wherein the at least one LED device is connected in series to a half wave rectifier.

MUL-0005

9. (previously presented) A retrofit LED light tube for replacing a fluorescent light tube in a troffer fixture, the LED retrofit light tube comprising:

an elongated cylindrical transparent envelope, wherein the envelope comprises a first half and a second half, wherein the halves are complementary and adapted to form the envelope;

a base cap at each end of the envelope, wherein the base cap comprises a first prong and a second prong extending from the base cap, wherein the first and second prongs are adapted to electrically communicate with a fluorescent light socket; and

at least one LED device in electrical communication with the base cap, wherein a positive terminal of the LED device is in electrical communication with the first prong and a negative terminal is in electrical communication with the second prong.

10. (previously presented) The retrofit LED light tube of Claim 9, wherein the LED device comprises an organic light emitting diode.

11. (previously presented) The retrofit LED light tube of Claim 9, wherein the at least one LED device are connected in parallel to additional LED devices.

12. (previously presented) The retrofit LED light tube of Claim 9, further comprising a means for protection against a voltage surge.

MUL-0005

13. (previously presented) The retrofit LED light tube of Claim 12, wherein the means for protection against a voltage surge comprises a varistor positioned in parallel with the at least one LED device.

14. (previously presented) The retrofit LED light tube of Claim 9, wherein the LED device comprises a circuit board and a plurality of LEDs serially connected to the circuit board.

15. (previously presented) The retrofit LED light tube of Claim 9, wherein the at least one LED device is connected in series to a half wave rectifier.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**